

efi max

Moves together until destinations!



SALES ORGANIZER

Efimax

Efimax lubricants are an attractive choice for all automotive professionals and end customers. Efimax has its origins in the Netherlands. The range of Efimax consists of different categories and within this we offer several products. Installations specially developed to produce lubricants provide efimax with an unprecedented high and continuous grade of quality. The laboratory is constantly working on improving existing oils and developing new products. They form the basis of the extensive range of e-products as we know them, which meet the most recent requirements of Original Equipment Manufacturers. producers. Due to our experience and knowledge in the field, efimax offers products with optimized performance for every application. All technological developments are followed closely to provide our lubricants with the right properties for maximum and safe performance. This catalogue provides an overview of our products and the associated information.



CONTENT

AUTOMOTIVE: PASSENGER CARS

EM30051	OxyTech 5W-30 C2	5
EM30052	OxyTech 5W-30 C3	5
EM30053	OxyTech 5W-20 MS-FE	5
EM30054	ViscoTech 10W-40 B4 DIESEL	6
EM30055	ViscoTech 20W-50 SL/CF	6

AUTOMOTIVE: HEAVY DUTY

EM30056	TechnoTech 10W-40	6
EM30057	ViscoTech 15W-40 CI4	7
EM30058	ViscoTech 15W-40 CH4	7

TRANSMISSION FLUIDS

EM30059	OxyTech 80W-90 GL5	7
EM30060	TechnoTech ATF DIII	8
EM30061	OxyTech Multi Vehicle ATF	8
EM30062	OxyTech ATF Life Protect 6	8
EM30063	ViscoTech 85W-140 GL5	9
EM30064	OxyTech ATF MB	9

BRAKE & STEERING FLUIDS

EM30085	efimax DOT 3&4	9
---------	----------------	---

COOLANTS

EM30065	ModernTech Coolant -36 ° C Longlife G12+	10
EM30066	ModernTech Coolant -36° C Longlife G13	10

CONTENT

MARINE

EM30070	Outboard 4T 10W-30	11
EM30071	Outboard 4T 25W-40	11
EM30072	Universal 2T Bio	11

AGRICULTURE

EM30073	TractoFluid 100	12
EM30074	Tractofluid 170	12

INDUSTRIES

EM30075	Indo ISO 32	12
EM30076	Indo ISO 46	13
EM30077	Indo ISO 68	13
EM30078	Indo Heat Transfer Oil 32	13

MOTOR CYCLE

EM30079	Moto 4T 10W-40	14
EM30080	Moto 4T 15W-50	14
EM30081	Moto 4T 20W-50	14
EM30082	Fork Oil 10W	15

GREASE

EM30083	Multipurpose Grease 2	15
EM30084	Lithium Grease EP 2	15

AUTOMOTIVE: PASSENGER CARS

Available packing: 1L - 5L - 20L - 210L



PRODUCTCODE: **EM30051**

EFIMAX

OxyTech 5W-30 C2

This is a full synthetic lubricant based on carefully selected very high quality base oils. This high-performance engine oil with low viscosity is specifically developed to provide the highest fuel economy and lowest CO2 emissions.

Performance

ACEA: C2-16
API: SN/CF
FIAT: 9.55535-S1
PSA: B71 2290
RENAULT: RN 0700



PRODUCTCODE: **EM30052**

EFIMAX

OxyTech 5W-30 C3

This is a full synthetic lubricant based on carefully selected very high quality base oils, formulated using the latest technology for Mid SAPS catalyst compatible engine oils. Its special formulation combines fuel economy with an extended service life. The reduced ash formulation protects particulate filters and exhaust after-treatment devices.

Performance

ACEA: C2*
ACEA: C3-16
API: SN/CF
BMW: LONGLIFE-04
FIAT: 9.55535-S3
GM: dexos2™

MB: 229.51
MB: 229.52
VW: 502 00
VW: 505 00
VW: 505 01



PRODUCTCODE: **EM30053**

EFIMAX

OxyTech 5W-20 MS-FE

This is a full synthetic lubricant based on carefully selected very high quality base oils, formulated using the latest technology for Mid SAPS catalyst compatible engine oils. Its special formulation combines fuel economy with an extended service life. The reduced ash formulation protects particulate filters and exhaust after-treatment devices.

Performance

ACEA: A1/B1-12
ACEA: C5-16
API: SN
FORD: WSS-M2C948-A
FORD: WSS-M2C948-B
ILSAC: GF-5
JAGUAR-LAND ROVER: STJLR.03.5004

AUTOMOTIVE: PASSENGER CARS



PRODUCTCODE: **EM30054**

EFIMAX

ViscoTech 10W-40 B4 DIESEL

This is a semi synthetic lubricant based on carefully selected highly refined base oils. It is designed for the lubrication of four-stroke diesel cars, including diesel engines with direct injection such as Common Rail, HDI, CDI, etc. The use of high-quality components ensures that the oil has a great fluidity at low temperature and a stable viscosity at high temperatures. Its low ash formulation is combined with a high resistance to ageing.

Performance

ACEA: A3/B3-10
ACEA: A3/B4-08
API: SL/CF
MB: 229.1
VW: 501 01
VW: 505 00



PRODUCTCODE: **EM30055**

EFIMAX

ViscoTech 20W-50 SL/CF

A very high quality mineral engine oil, which is suitable for most of 4-stroke gasoline and diesel cars and light trucks. By its selected composition, a very good resistance to oxidation and optimal detergent and dispersion properties are obtained. A strong oil film guarantees a high lubricating power.

Performance

ACEA: A3/B3-10
ACEA: A3/B4-08
API: SL/CF
MB: 229.1
VW: 501 01 Level
VW: 505 00 Level

AUTOMOTIVE: HEAVY DUTY



PRODUCTCODE: **EM30056**

EFIMAX

TechnoTech 10W-40

Universal mineral engine oil with higher TBN designed to meet the latest specifications of both European and American manufacturers of heavy diesel engines. This oil is suitable for low-emission engines (Euro II, Euro III and some Euro IV engines). It is not suitable for Euro IV engines with particulate filter. It provides excellent protection against deposits an improved protection against camshaft wear and it allows very long drain intervals.

Performance

ACEA: A3/B4-10
ACEA: E7-08 Issue 2
ALLISON : C4
API: CG-4
API: CH-4
API: CI-4/SL
CATERPILLAR: ECF-1a
CATERPILLAR: ECF-2
CUMMINS: CES 20076
CUMMINS: CES 20077
CUMMINS: CES 20078
DETROIT DIESEL: 93K215
DEUTZ: DQC-III-10
GLOBAL: DHD-1
JASO: DH-1
MACK: EO-M PLUS

MACK: EO-N PLUS
MAN: M3275-1
MB: 228.3
MB: 229.1
MTU: Oil Category 2
RENAULT: RLD
RENAULT: RLD-2
VOLVO: VDS-3

Available packing: 1L / 5L / 20L / 210L

AUTOMOTIVE: HEAVY DUTY



PRODUCTCODE: **EM30057**

EFIMAX

ViscoTech 15W-40 CI4

This is a high-performance mineral diesel engine oil formulated to deliver reliable performance in a broad range of heavy-duty applications. It is suitable for low-emission engines (Euro II, Euro III and some Euro IV engines).

Performance

ACEA: A3/B4-12
ACEA: E7-16
ALLISON : C4
API: CG-4
API: CH-4
API: CI-4/SL
CATERPILLAR: ECF-1a
CATERPILLAR: ECF-2
CUMMINS: CES 20076
CUMMINS: CES 20077
CUMMINS: CES 20078
DETROIT DIESEL: 93K215
DEUTZ: DQC-III-10

GLOBAL: DHD-1
JASO: DH-1
MACK: EO-M PLUS
MACK: EO-N
MAN: M3275-1
MB: 228.3
MB: 229.1
MTU: Oil Category 2
RENAULT: RLD
RENAULT: RLD-2
VOLVO: VDS-3



PRODUCTCODE: **EM30058**

EFIMAX

ViscoTech 15W-40 CH4

Universal engine oil, designed to meet the latest specifications of both European and American manufacturers of heavy diesel engines. This oil is suitable for low-emission engines (Euro II and Euro III and some Euro IV engines); it is not suitable for Euro IV engines with particulate filter. It provides excellent protection against deposits in pipes and turbo engine, an improved protection against camshaft wear and it allows very long drain intervals.

Performance

ACEA: A3/B4-10
ACEA: E5 Level
ALLISON : C4
API: CH-4/SJ
CATERPILLAR: ECF-1a
CUMMINS: CES 20071
CUMMINS: CES 20072
CUMMINS: CES 20076
CUMMINS: CES 20077
DEUTZ: DQC II-05
MACK: EO-M PLUS
MAN: M3275-1
MB: 228.3

MB: 229.1
MTU: Oil Category 2
RENAULT: RD-2
VOLVO: VDS-2

TRANSMISSION FLUIDS



PRODUCTCODE: **EM30059**

EFIMAX

OxyTech 80W-90 GL5

This is a synthetic based lubricant for transmissions, which distinguishes itself from the classic, hypoid GL 5-oils by its multifunctional character and its exceptional oxidation and thermal stability.

Performance

API: GL-4
API: GL-5
API: MT-1
ARVIN MERITOR: 0-76-N
DAF: GL5/MIL-PRF-2105E
IVECO: MIL-PRF-2105E
MACK: GO-J
MAN: 341 E-2
MAN: 341 Z-2
MAN: 342 M-2
MB: 235.0
MIL: PRF-2105E
RENAULT: B0032/3 Annex 3
SAE: J 2360
SCANIA: STO 1
ZF: TE-ML 02B

ZF: TE-ML 05A
ZF: TE-ML 07A
ZF: TE-ML 08
ZF: TE-ML 12E
ZF: TE-ML 12L
ZF: TE-ML 12M
ZF: TE-ML 16B
ZF: TE-ML 16C
ZF: TE-ML 16D
ZF: TE-ML 17B
ZF: TE-ML 19B
ZF: TE-ML 21A

Available packing 1L / 5L / 20L / 210L

TRANSMISSION FLUIDS

Available packing 1L / 5L / 20L / 210L



PRODUCTCODE: **EM30060**

EFIMAX TechnoTech ATF DIII

This is a semi synthetic lubricant based on carefully selected highly refined base oils. This is an oil with a very high viscosity index for most automatic transmissions. The improved fluidity at low temperatures ensures optimum performance in all conditions. Its exceptional frictional characteristics provide smooth switching and driving comfort.

Performance

ALLISON : C4
FORD: MERCON
GM: 6417-M DEXRON III-G
MAN: 339 V1/Z1
MB: 236.5
MB: 236.9
VOITH: H55.6335xx
VOLVO: STD 1273,40 (97340)
VOLVO: STD 1273,41 (97341)
ZF: TE-ML 03D
ZF: TE-ML 04D
ZF: TE-ML 09
ZF: TE-ML 11B

ZF: TE-ML 14A
ZF: TE-ML 17C



PRODUCTCODE: **EM30061**

EFIMAX OxyTech Multi Vehicle ATF

This is a full synthetic lubricant based on carefully selected very highly refined base oils for automatic transmissions , meeting the requirements of most American, Japanese and European manufacturers.

Performance

ALLISON-WARNER: JWS 3309
ALLISON-WARNER: JWS 3314
ALLISON-WARNER: JWS 3317
ALLISON : TES 295
BMW: ETL 7045E
BMW: ETL 8072B
BMW: LA 2634
BMW: LT 71141
CHRYSLER: ATF +3 AND +4
FIAT: 955550-AV4
FORD: MERCON V
FORD: WSS-M2C922-A1
GM: DEXRON III-H
HONDA: ATF Z-1
HYUNDAI: SP-III
MB: 236.10

MB: 236.11
MB: 236.3
MB: 236.7
NISSAN: MATIC-K
NISSAN: MATIC-W
PSA: P/N Z 000169756
TOYOTA: TYPE T-IV
VW: G 052 055
VW: G 052 162
VW: G 052 533
VW: G 052 990



PRODUCTCODE: **EM30062**

EFIMAX OxyTech ATF Life Protect 6

This is a full synthetic lubricant based on carefully selected very high quality base oils that has been specifically developed for ZF 6-speed automatic transmissions. Its particular formulation ensures a trouble-free operation and smooth gear shifting.

Performance

AML: 4G4319A509/AA/S
BENTLEY: PY112995PA
BMW: 83220142516
BMW: M-13754
HYUNDAI: 040000C905G

JAGUAR: Fluid 8432
LAND ROVER: TYK500050
MASERATI: 231603
VW: G 055 005
ZF: TE-ML 11

TRANSMISSION FLUIDS



EFIMAX ViscoTech 85W-140 GL5

This is an extreme-pressure lubricant for gear boxes, specifically formulated to satisfy the highest service conditions: high speed, shockloads and high torque at low speeds.

Performance

API: GL-5
MIL: MIL-L-2105 C
MIL: MIL-L-2105 D
ZF: TE-ML 05A
ZF: TE-ML 07A
ZF: TE-ML 12E

ZF: TE-ML 16B
ZF: TE-ML 16C
ZF: TE-ML 16D
ZF: TE-ML 17B
ZF: TE-ML 19B

PRODUCTCODE: **EM30063**



EFIMAX OxyTech ATF MB

This is a full synthetic lubricant based on carefully selected very high quality base oils, mainly intended for all MB 7-speed automatic transmissions and NAG-V Sport transmissions. It provides excellent frictional durability and superior performance.

Performance

MB: 236.14

PRODUCTCODE: **EM30064**

BRAKE & STEERING FLUIDS

Available packing 250ML / 500ML / 1L / 4L



EFIMAX efimax DOT 3&4

Brake fluid, intended for hydraulic brake systems. Its composition provides a high chemical stability, excellent resistance against residue formation, very good stability towards oxidation and is compatible with all materials present in the circuit.

Performance

FMVSS: 116 DOT 4
FMVSS: 116 DOT3
ISO: 4925 Class 3&4
SAE: J 1703
SAE: J 1704

PRODUCTCODE: **EM30085**

COOLANTS

Available packing: 1L / 5L / 20L / 210L



PRODUCTCODE: **EM30065**

EFIMAX

ModernTech Coolant -36 °C Longlife G12+

A diluted on ethylene glycol based coolant for use in engines. It employs Organic Acid Technology (OAT) inhibitor and is nitrite, amine and phosphate (NAP) free. It is also free of borate and silicate. The sophisticated technology provides superior and permanent protection to all components of the cooling system and a life span of 4 - 6 years or 250.000 km for passenger cars and 500.000 km for professional applications. Ready to use solution.

Performance

AFNOR: NF R 15-601
ASTM: D3306
ASTM: D4985
BS: 6580
CUMMINS: 85T8-2
CUMMINS: 90T8-4
DAF: 74002
DEUTZ: 0199-99-1115
FFV: Heft R443
FORD: WSS-M97B44-D
GM: 1825M
GM: 1899M
GM: 6277M
JASO: M325
JD: H24B1/C1
JD: JDM H5
KOMATSU: 07892

LIEBHERR: MD1-36-130
MAN: 324 SNF
MB: 325.2
MB: 325.3
MITSUBISHI: MHI
MTU: MTL 5048
NATO: S759
OPEL: GM QL 130100
POLISH STANDARD:
PN-C-40007
PSA: B71 5110
RENAULT: 41-01-001
SAE: J1034
SCANIA: TB 1451
VOLVO: 128 6083/002
VW: TL 774-D
VW: TL 774-F



PRODUCTCODE: **EM30066**

EFIMAX

ModernTech Coolant -36 °C Longlife G13

A diluted on ethylene glycol/glycerine based coolant for use in engines. It employs Hybrid Organic Acid Technology (HOAT) inhibitor, is nitrite, amine, phosphate (NAP) and borate free. It contains some silicate additives which gives a fast healing aluminium protection. This technology provides superior and permanent protection to all components of the cooling system and a life span of 4 - 6 years or 250.000 km for passenger cars and 500.000 km for professional applications. Ready to use solution.

Performance

ASTM: D3306
VW: TL 774-J

Available packing 1L / 5L / 20L / 210L



PRODUCTCODE: **EM30070**

EFIMAX

Outboard 4T 10W-30

This is a semi synthetic lubricant based on carefully selected highly refined base oils. This 4-stroke motor oil is specifically designed to meet the requirements of the NMMA FC-W specification. This oil procures an increased protection against corrosion, even in a salt water environment. It also contains a unique anti-wear package based on molybdenum/zinc technology.

Performance

API: SJ

API: SL

NMMA: FC-W



PRODUCTCODE: **EM30071**

EFIMAX

Outboard 4T 25W-40

This is a semi-synthetic 4-stroke motor oil, specifically designed to meet the requirements of the NMMA FC-W specification. This oil procures an increased protection against corrosion, even in a salt water environment. It also contains a unique anti-wear package based on molybdenum/zinc technology.

Performance

API: SJ

API: SL

NMMA: FC-W



PRODUCTCODE: **EM30072**

EFIMAX

Universal 2T Bio

This is a full synthetic lubricant based on carefully selected very high quality base oils for water-cooled 2-stroke gasoline engines, with a very high output. Can also be used for air-cooled engines. Biodegradable and universally applicable, this oil is suited for machines where the tank is filled with a mixture of gasoline and oil, and for those with separate oil reservoirs. Easily miscible with gasoline and excellent protection against rust and deposits.

Performance

API: TC+

CEC: L-33-A-93

NMMA: TC-W3

AGRICULTURE

Available packing 1L / 5L / 20L / 210L



PRODUCTCODE: **EM30073**

EFIMAX TractoFluid 100

Special oil designed for automatic transmissions, hydraulic systems, brakes and clutches of tractors, forklifts and off-road equipment. This oil (Universal Tractor Transmission Oil) should never be used to lubricate the engine. When the manufacturer requires an oil for the lubrication of all parts including the engine, he refers to a super tractor oil universal.

Performance

ALLISON : C3
API: GL-4
CASE: IH HY-TRAN B6
CASE: IH HY-TRAN PLUS
CASE: MS1204
CASE: MS1207
CASE: MS1209
CASE: MS1210
CATERPILLAR: TO-2

FORD: ESN-M2C-41 A/B
JCB: SPECIAL HYDRAULIC FLUID
MF: M 1110
MF: M 1141



PRODUCTCODE: **EM30074**

EFIMAX Tractofluid 170

Special oil designed for automatic transmissions, hydraulic systems, brakes and clutches of tractors, forklifts and off-road equipment. This oil (Universal Tractor Transmission Oil) should never be used to lubricate the engine. When the manufacturer requires an oil for the lubrication of all parts, including the engine, he refers to a super tractor oil universal.

Performance

ALLISON : C3/C4
API: GL-4
CASE: MAT 3505
CASE: MAT 3525
CATERPILLAR: TO-2
FORD: ESN-M2C-134 C/D
FORD: ESN-M2C-86 C
FORD: M2C-86A

JD: J20 C/D
MF: M 1127
MF: M 1129A
MF: M 1143
NH: NH 410B
ZF: 03E
ZF: 05F
ZF: 17E

INDUSTRIES

Available packing 1L / 5L / 20L / 210L



PRODUCTCODE: **EM30075**

EFIMAX Indo ISO 32

A mineral oil, specifically designed to meet the requirements of most important manufacturers of hydraulic equipment. It contains anti-wear, anti-oxidant, anti-corrosion and anti-foam additives.

Performance

AFNOR: NF E 48-603 HM
AFNOR: NF E 48-690
AFNOR: NF E 48-691
ASTM: D6158 HL, HM
BOSCH REXROTH: RDE 90235
CHINESE STANDARD: GB 11118.1 L-HL, L-HM
CINCINNATI: MACHINE P-68 (ISO 32)
DANIELI: 0.000.001Rev.15 Typ 10/11
DENISON: HF-0, HF-1, HF-2
DIN: 51524 Part 2

EATON VICKERS: I-286-S
EATON VICKERS: M-2950-S
EATON: Brochure 03-401-2010
EATON: E-FDGN-TB002-E
GM: LS2 AW hyd.oil
ISO: 11158, HM
ISO: 6743-4, HM
JCMAS: HK P041
SAE: MS1004
US STEEL: 126
ZF: TE-ML 07H

Available packing 1L / 5L / 20L / 210L



PRODUCTCODE: **EM30076**

EFIMAX

Indo ISO 46

A mineral oil specifically designed to meet the requirements of most important manufacturers of hydraulic equipment. It contains anti-wear, anti-oxidant, anti-corrosion and anti-foam additives.

Performance

AFNOR: NF E 48-603 HM
AFNOR: NF E 48-690
AFNOR: NF E 48-691
ASTM: D6158 HL, HM
BOSCH REXROTH: RDE 90235
CHINESE STANDARD: GB 11118.1 L-HL, L-HM
CINCINNATI: MACHINE P-70 (ISO 46)
DANIELI: 0.000.001Rev.15 Typ 10/11
DENISON: HF-0, HF-1, HF-2
DIN: 51524 Part 2

EATON VICKERS: I-286-S
EATON VICKERS: M-2950-S
EATON: Brochure 03-401-2010
EATON: E-FDGN-TB002-E
GM: LS2 AW hyd.oil
ISO: 11158, HM
ISO: 6743-4, HM
JCMAS: HK P041
SAE: MS1004
US STEEL: 126
ZF: TE-ML 07H



PRODUCTCODE: **EM30077**

EFIMAX

Indo ISO 68

A mineral oil, specifically designed to meet the requirements of most important manufacturers of hydraulic equipment. It contains anti-wear, anti-oxidant, anti-corrosion and anti-foam additives.

Performance

AFNOR: NF E 48-603 HM
AFNOR: NF E 48-690
AFNOR: NF E 48-691
ASTM: D6158 HL, HM
BOSCH REXROTH: RDE 90235
CHINESE STANDARD: GB 11118.1 L-HL, L-HM
CINCINNATI: MACHINE P-69 (ISO 68)
DANIELI: 0.000.001Rev.15 Typ 10/11
DENISON: HF-0, HF-1, HF-2
DIN: 51524 Part 2

EATON VICKERS: I-286-S
EATON VICKERS: M-2950-S
EATON: Brochure 03-401-2010
EATON: E-FDGN-TB002-E
GM: LS2 AW hyd.oil
ISO: 11158, HM
ISO: 6743-4, HM
JCMAS: HK P041
SAE: MS1004
US STEEL: 126
ZF: TE-ML 07H



PRODUCTCODE: **EM30078**

EFIMAX

Indo Heat Transfer Oil 32

This is a heat transfer oil based on a specifically refined mineral oil with exceptional oxidation stability and very high resistance to thermal decomposition.

Performance

ISO: 32

MOTOR CYCLE

Available packing 1L / 4L / 20L / 210L



PRODUCTCODE: **EM30079**

EFIMAX

Moto 4T 10W-40

This is a semi synthetic lubricant based on carefully selected highly refined base oils. This oil is for 4-stroke engines for normal and intensive use. Based on an enforced formula with extreme pressure additives for gear boxes. Its special formulation avoids slipping of the wet clutches and has excellent dispersant and detergent action. It offers optimum protection and longer lifetime of the engine.

Performance

API: SL
JASO: MA
JASO: MA2



PRODUCTCODE: **EM30080**

EFIMAX

Moto 4T 15W-50

This is a semi synthetic lubricant based on carefully selected highly refined base oils. This oil is for 4-stroke engines for normal and intensive use. Based on an enforced formula with extreme pressure additives for gear boxes. Its special formulation avoids slipping of the wet clutches and has excellent dispersant and detergent action. It offers optimum protection and longer lifetime of the engine.

Performance

API: SL
JASO: MA
JASO: MA2



PRODUCTCODE: **EM30081**

EFIMAX

Moto 4T 20W-50

This is a full synthetic lubricant based on carefully selected very high quality base oils. This oil is for 4-stroke engines for normal and intensive use. Based on an enforced formula with extreme pressure additives for gear boxes. Its special formulation avoids slipping of the wet clutches and has excellent dispersant and detergent action. It offers optimum protection and longer lifetime of the engine.

Performance

API: SL
JASO: MA
JASO: MA2

MOTOR CYCLE



PRODUCTCODE: **EM30082**

EFIMAX Fork Oil 10W

This fork oil is based on mineral base oils with a very high viscosity index. This will provide optimum dampening control over a wide temperature range in any circumstances (on- and off-road). Its excellent anti-corrosion and anti-wear properties will contribute to long service life. This lubricant also has quick air release, low foaming tendency and excellent elastomer compatibility.

Performance
DIN: 51524 Part 3

GREASE



PRODUCTCODE: **EM30083**

EFIMAX Multipurpose Grease 2

This is a lubricating grease for general applications, where no specific requirements are made. This lithium based grease has a good oxidation stability, so that it can ensure long-lasting lubrication. It is water-resistant and has good temperature characteristics. Therefore it can be used at high temperatures and it stays pumpable at low temperatures making it suitable for bearing lubrication.

Performance
DIN: 51502
DIN: K2K-30
ISO: 6743
ISO: L-XCCEA2



PRODUCTCODE: **EM30084**

EFIMAX Lithium Grease EP 2

This is a grease with high-pressure properties, for heavily loaded applications in general. This grease has a good oxidation stability and anti-wear properties. It can ensure long-lasting lubrication. It is water-resistant and shows good temperature characteristics. It can be used at high temperature and stays pumpable at low temperatures making it suitable for heavily loaded bearings as well as wet environments.

Performance
DIN: 51502
DIN: KP2K-30
ISO: 6743
ISO: L-XCCIB2

Additives :



Engine Flush



Radiator Cleaner



Oil Leak Stopper



Injector Cleaner
(Diesel)

Production Factory :

Rotterdam, Holland

Middle East Marketing Office :

Safalah Overseas Co LLC.

P.O. BOX : 26

Salalah : 211

Sultanate of Oman

Phone: +968 232 108 81 / 92832552

Fax: +968 232 120 61

E-mai: info@efimaxoil.com

www.efimaxoil.com

